

Please replace the second sentence in the paragraph beginning at page 3, line 2, with the following rewritten sentence:

--The assembly 1 includes a first layer 10, a second layer 20, and a third layer 30, which third layer 30 is contained entirely within the second layer 20.

Please replace the second sentence in the paragraph beginning at page 3, line 10, with the following rewritten sentence:

--The closure 13 defining an access opening 13C to the cavity 12 within the first layer 10, said access opening 13C adapted to receive the second layer 20 as will be further discussed.

Please replace the second sentence in the paragraph beginning at page 3, line 17, with the following rewritten sentence:

--The closure 13 includes a fastening means 40, said fastening means 40 preferably including a first fastening member 40A and a second fastening member 40B, said fastening means 40 preferably a Velcro. RTM - type material having a strip of loop material (not shown) and a matching strip of hook material (not shown).

Please replace the third sentence in the paragraph beginning at page 3, line 17, with the following rewritten sentence:

--For example, the strip of loop material, representing the second fastening member 40B, may be positioned on the outer side of the first edge 13A, and the hook material, representing the first fastening member 40A, is transversely positioned along the inner side of the second edge 13B.

Please replace the fifth sentence in the paragraph beginning at page 3, line 17, with the following rewritten sentence:

--It is further understood by one skilled in the art that the fastening means 40 of the closure 13 may further consist of any other fastening means common in the art, such as a zipper, snaps, buttons, and the like.

Please replace the second sentence in the paragraph beginning at page 3, line 29, with the following rewritten sentence:

--The second layer 20 is then secured in position within the first layer 10 by said fastening means 40.

Please replace the paragraph beginning at page 4, line 6, with the following rewritten paragraph:

--In the preferred embodiment of the present invention, the third layer 30 is contained entirely within the second layer 20, said third layer 30 is a foam-type material, preferably a shredded foam-fill material. Such foam material of the third layer 30 further suitable to conform to the said rectangular configuration of the second layer 20 when the second layer 20 is not stored within the first layer 10. Such foam material of the third layer 30 further suitable to conform to the shape of the first layer 10 when storing the second layer 20 therein. As such, the third layer 30 is a foam padding inside the second layer 20 when the second layer 20 is used as a bed; and when the second layer 20 is stored within the first layer 10, the third layer 30 is a foam padding for when the first layer 10 is used as a seating apparatus. It should be understood that the thickness of the second layer 20 is dependent upon the volume of foam material forming the third layer 30.--

Please replace the first sentence of the paragraph beginning at page 4, line 18, with the following rewritten sentence: